

# Gruett's Inc

*"Lineup Of Quality Farm Equipment"*

## Tandem Axle Wagons



### **G24T 12-TON**

•74" Thread Width, 2" Spindles, 6 Bolt 10" X 15" Rims Standard, All Welded Construction, One Piece Spindles, Bolster Stakes At 42" Spacing, Tow Hitch Plate Standard, Grease Fittings For Proper Lubrication, Automotive Type Steering, Tie Rods Located Behind A Hefty Box Axle, WishBone Type Tandem Axle For Excellent Mud Clearance And Hugs The Ground For A Smoother Ride Over Rough Terrain, Heavy Duty Telescoping Pole And Spring Assist Standard

### **G28T 14-TON**

•78" Thread Width, 2 1/4" Spindles, 8 Bolt 10" X 15" Rims Standard, All Welded Construction, One Piece Spindles, Bolster Stakes At 42" Spacing, Tow Hitch Plate Standard, Grease Fittings For Proper Lubrication, Automotive Type Steering, Tie Rods Located Behind A Hefty Box Axle, WishBone Type Tandem Axle For Excellent Mud Clearance And Hugs The Ground For A Smoother Ride Over Rough Terrain, Heavy Duty Telescoping Pole And Spring Assist Standard

### **G36T 18-TON**

•80" Thread Width, 2 3/4" Spindles, 8 Bolt 10" X 16" Rims Standard, All Welded Construction, One Piece Spindles, Bolster Stakes At 42" Spacing, Tow Hitch Plate Standard, Grease Fittings For Proper Lubrication, Automotive Type Steering, Tie Rods Located Behind A Hefty Box Axle, Double Webbing Type Tandem Axle For Greater Strength, WishBone Type Axle For Excellent Mud Clearance And Hugs The Ground For A Smoother Ride Over Rough Terrain, Heavy Duty Telescoping Pole And Spring Assist Standard


Ball Joint Steering  
On All Wagons



WishBoneType Tandem  
Axles On All Wagons



Double Webbing On G36T  
18 Ton Wagon



Designs And Specifications Are Subject To Change Without Notice

101 Main Street, Potter, Wi 54160

920-853-3516

# Gruett's Inc

*"Lineup Of Quality Farm Equipment"*

## 22 Ton Tandem Axle Wagon



Ball Joint  
Steering On  
All Wagons



Surge  
Brakes Are  
Standard



### G44T 22-TON

•85" Thread Width, 3" Spindles, 8 Bolt 11" X 22.5" Rims Standard, All Welded Construction, One Piece Spindles, Bolster Stakes At 42" Spacing, Tow Hitch Plate Standard, Grease Fittings For Proper Lubrication, Automotive Type Steering, Tie Rods Located Behind A Hefty Box Axle, Double Webbing Type Tandem Axle For Greater Strength, WishBone Type Axle For Excellent Mud Clearance And Hugs The Ground For A Smoother Ride Over Rough Terrain, Heavy Duty Telescoping Pole And Spring Assist Standard, 4 Wheel Surge Brakes Are Standard

Designs And Specifications Are Subject To Change Without Notice

101 Main Street, Potter, WI 54160

920-853-3516